

Name of work :- Water proofing treatment of roof of thirty ADMS in Delhi and New Delhi during 2015-16

SCHEDULE OF WORK

S.NO.	Description of items	qty.	unit	rate	amount (Rs.)
1.	Cement plaster 1:3(1 cement: 3 coarse sand) finished with a floating coat of neat cement 12 mm thick cement plaster.	600.00	sqm	-----	-----
2.	Providing and laying water proofing treatment on roof of slabs by applying cement slurry mixed with water proofing cement compound consisting of applying: a) after surface preparation, first layer of slurry of cement @0.488kg/sqm mixed with water proofing cement compound @0.253 kg/sqm. b) laying second layer of fibre glass cloth when the first layer is still green. Overlapping of joints of fibre cloth should not be less than 10 cm c) third layer of 1.5 mm thickness consisting of slurry of cement @ 1.289 kg/sqm mixed with water proofing cement compound @ 0.670 kg/sqm and coarse sand @1.289 kg/sqm . This will be allowed to air cure for 4 hours followed by water curing for 48 hours. The entire treatment will be taken up to 30 cm on parapet wall and tucked into groove in parapet all around. d) Fourth and final layer of brick tiling with cement mortar (which will be paid for separately. For the purpose of measurement the entire treated surface will be measured.	300.00	sqm	-----	-----
3.	Extra for providing and mixing water proofing material in cement plaster work in proportion recommended by the manufacturers (Dr. Fixit brand will be used)	60 bags	per bags of 50 kg Cement used in the mix	-----	-----
Total cost of work: -					-----

CONDITIONS: AS ENCLOSED



